

Custom Permanent Party Marquee Tents White For Outdoor Events Luxury Party Marquee

Our Product Introduction

Basic Information

- Place of Origin: Guangdong
- Brand Name: Tendars
- Certification: ISO9001, SGS, Coc, CE
- Model Number: Big tent
- Minimum Order Quantity: 25 square meters
- Price: Reconsideration
- Packaging Details: 1, The aluminium frame structure packed into the bubble film 2, the pvc fabric roof cover and sidewalls are packed into the PVC fabric carry bag; 3, Hardware packed into the box.
- Delivery Time: 18days or To be negotiated
- Payment Terms: L/C, T/T, Western Union, MoneyGram
- Supply Ability: 50000 Square Meters per Month




Product Specification

- Features: UV Resistant, Waterproof, Fire Retardant B1
- Product Name: A Top Party Marquee
- Frame: Surface Anodized Finish. Anti Rust, Hard Pressed Extruded Aluminium Alloy 6061/T6
- Tent Roof Fabric: 850g/sqm Block Out White PVC Fabric
- Size: To Be Customized
- Fabric Color Option: White, Blue, Yellow, Red, Transparent Or Customized
- Accessories: PVC Windows, Glass Door, Stake, Stake Puller, Rain Gutter, Lining And Curtain, Flooring System, Glass Walling System, Weight Plate, ABS/Sandwich Wall System
- Max. Allowed Windspeed: 80km/hr, 0.3kn/m2
- Highlight: Permanent Party Marquee Tents, Custom Party Marquee Tents, Outdoor permanent party tent



More Images



Product Description

Custom Permanent Party Marquee Tents White For Outdoor Events Luxury Party Marquee

Product Specification:

Main frame	Galvanized steel pipes
Surface treat method	Hot dip galvanized
Tent roof fabric	850g/sqm block out white PVC fabric
Wind load	100km/h or customized
Features	Water proof, UV resistance, fire retardant(DIN4102,B1,M2)
Certificate	TUV ISO9001:2015
Warranty	Aluminum frame for 10 years, PVC fabric for 5 years.
Application	Wedding, Party, Living, Glamping
Snow load	25kg/sqm (snow can't stay if use big degree roof pitch design)
Allowed temperature condition	-30 degree Celsius~+70 degree Celsius

Features :

The tent is composed of a number of components, tarpaulin/fabric is one of the important components.

Tarpaulin/fabric the earliest time, the use of ordinary non-woven fabric, with the development of The Times, the progress of science and

technology, the current market is more popular Tarpaulin/fabric, has been replaced with pvc tarpaulin as a mainstream material. Domestic pvc

tarpaulin has B1 class fire, flame retardant, rain, anti-ultraviolet, surface self-cleaning function, simple washing can clean Tarpaulin/fabric. Strong

heat resistance, adaptability between -30°C and 70°C, reaching the standards of export to Europe and the United States. The Tarpaulin/fabric has

good relaxation and can be cut according to the frame to perfectly adapt to the frame of various materials. Whether it is a simple tent frame, or an

aluminum alloy frame, according to different configurations, with different buckle, you can perfectly adapt.

With the development and progress of science and technology, the strength and risk resistance of the tent are getting better and better

Fixing method :

The common building ground of the tent is grass, cement, asphalt, marble, mud, etc. We provide different fixed ways for different ground.

1. Steel fixation (short-term use)

This fixing method is generally used for soft lawns and mud, and the steel needs to be inserted into the soil through the footing. The general length of the steel is about 1m.



2. Embedded reinforced concrete (permanent use)

Under normal circumstances, it is used for a long time, and this kind of embedment has strong stability and high wind resistance level. In general, the warehouse tent, the basketball tent, the fixed way used in these permanent buildings, the footing and the embedded parts are welded to make the tent more solid.



3. Secure with expansion screws

The premise of this method of fixation is that the ground can be destroyed. Short-term and long-term use can be fixed in this way, the use of expansion screws fixed must ensure that the ground hardening thickness of 15cm.



4. Bearing disk The bearing frame is secured

This fixed way is used when the ground can not be damaged, such as indoor activity tents, promotional tents, etc. Bearing no general use is cement stone, sand, iron frame to do bearing material.

**FAQ :****The safety of the tent?**

The safety performance of the tent mainly looks at two aspects: First, the profile used in the tent, the profile used in our aluminum alloy tent frame is 6061-T6, followed by the model used in our tent, the model used in different spans is very particular. The wind resistance levels that different models and thicknesses can withstand are different. We have to choose the right model according to the region, and the larger the model, the more expensive it is. Some manufacturers choose some low-end materials in order to reduce prices.

How long can the canopy span?

Our tent is a modular building, its span can range from 3-60 meters span, the length can be 3 meters or 5 meters a room to extend indefinitely. With the modular construction of the canopy, our canopy building can be used repeatedly.

Will it be hot in the tent?

The cloths around the canopy can be opened for ventilation, and large ceiling fans and air conditioning can also be installed inside the canopy. Large tent, we can provide special tent air conditioning, under normal circumstances, the home air conditioning can fully meet the temperature of the tent.

Contact us :

Company:	Tendars technology Co.,Ltd
Address:	Room 904, No. 6, Hanxing 3rd Street, Zhongcun Street, Guangzhou, Guangdong, China
Contact person:	Amanda Chen
Tel:	0086-13640286461
Mobile(Wechat/Whatsapp):	+86 13640286461
Web:	http://www.marquees-tent.com



Guangzhou Tendars Tent Co., Limited

☎ 0086 13640286461

✉ amanda@marquees-tent.com

🌐 marquees-tent.com

No.319, 2nd building , 8th zone , Aoyuan city plaza , Zhongcun Street, Guangzhou, Guangdong, China