



Aluminum Alloy Commercial Heavy Duty Marquee Waterproof Fire Retardant Tents For House

Our Product Introduction

Basic Information

- Place of Origin: Guangdong
- Brand Name: Tendars
- Certification: ISO9001, SGS, Coc, CE
- Model Number: Big tent
- Minimum Order Quantity: 25 square meters
- Price: Reconsideration
- Packaging Details: 1, The aluminium frame structure packed into the bubble film 2, the pvc fabric roof cover and sidewalls are packed into the PVC fabric carry bag; 3, Hardware packed into the box.
- Delivery Time: 18days or To be negotiated
- Payment Terms: L/C, T/T, Western Union, MoneyGram
- Supply Ability: 50000 Square Meters per Month




Product Specification

- Features: Water Proof, UV Resistance, Fire Retardant(DIN4102)
- Product Name: A Frame Marquee
- Frame: Aluminum Alloy 6061-T6
- Roof Cover: Opaque(or Transparent), Water Proof, 850g/m². Flame Retardant.PVC-coated Polyester
- Width: Customized
- Water Repellency: Waterproof
- Options: Windows, Ventilations, Insulation, Doors, Curtain Kit, Etc
- Highlight: **Aluminum Alloy Commercial Heavy Duty Marquee**
, Commercial Heavy Duty Marquee Waterproof



More Images



Product Description

Aluminum Alloy Commercial Heavy Duty Marquee Waterproof Fire Retardant Tents For House

Description :

Item	Specification
Clear-span width	3m - 60m
Eave height	2.6m /3m/4m/5m/6m or customized
Ridge height	4.3 - 8m or customized
Roof pitch	20°
Longest component	3.7-10.6m
Minimum tent length	Can be customized
Roof fixing	Not limited
Main profile	84x48x3mm/ 122x68x3mm/ 166x88x3mm/ 203x112x4mm/ 204x112x4.5mm/ 256x120x5mm/ 300x125x5mm/ 350x126x6mm/ customized
Max.allowed wind speed	100km/hour ,0.5kn/m³ or can be customized
Eave/Ridge connection	Hot-dip Galvanized steel insert
Materials	(1) Frame structure: Hard pressed extruded aluminium 6061 /T6(15HW) which can last 15 to 25 years. (2) Fabric cover: High quality double PVC-coated polyester textile, 100% waterproof, flame retardant to DIN4102 B1, M2, CFM, UV resistant, tear resistant, self-cleaning ability, etc. (3) Connector: Strong hot-DIP galvanized steel
Features	(1) Allowed temperature condition: -30 degree Celsius~+70 degree Celsius (2) Wind load: Max. 80km/h (can be reinforced) (3) Snow load: 75kg/sqm (snow can't stay if use big degree roof pitch design) (4) Easy to be assembled and dismantled, movable. (5) No pole inside, 100% available interior space.
Optional accessories	(1) Covers: Colourful cover, transparent cover, inflatable roof cover (2) Windows: Dome or square clear PVC windows, mesh window, glass window for glass wall (3) Wooden flooring system: VIP cassette flooring, simple cassette flooring (4) Doors: Double-wing glass door, single-wing glass door, glass fire door, aluminium door, rolling shutter(automatic or manual) (5) Wall: Soft PVC fabric wall, glass wall, ABS hard wall, sandwich panel wall, steel plate wall (6) Fixing methods: Ground anchors, weight plate, expandable bolts Rain gutters (inner roof beam rain gutter or rain gutter between two similar tents) (7) Other optional items: Table, chair, lighting, AC, carpet, installation tools etc.

Why choose us ?

1. Advantage: competitive Advantage products.
2. MOQ:Sample offer & SMALL order welcomed .
3. Warranty period: Guarantee one year. During the warranty period, we shall repair or replace the damaged part accordingly because of any damage due to quality problem.
4. Confidentiality agreement : "business secret contract".
5. Assurance:quality Assurance contract

Ventilation design of warehouse tents :

The ventilation design of warehouse tents should consider the following aspects:

Roof ventilation: The roof of the warehouse tent should be equipped with appropriate skylights or vents so that it can be naturally ventilated in the case of high temperature or humidity, reduce the indoor temperature and humidity, and prevent the goods from being damaged by moisture or high temperature.

Side wall ventilation: The side wall of the warehouse tent can be equipped with openable windows or vents. When the outdoor air flows through, it can take away the moisture and heat in the room and keep the room dry and ventilated.

Ground ventilation: Appropriate drainage holes or vents should be set on the ground of the warehouse tent to discharge indoor moisture and heat in time and keep the room dry and ventilated.

Selection of ventilation equipment for warehouse tents :

The ventilation equipment of the warehouse tent mainly includes exhaust fans, ventilation ducts, filters, etc. Here are a few things to look out for when choosing a ventilator:

Air volume: Calculate the required air volume according to the warehouse area and environmental conditions, and choose the appropriate air volume.

Noise: Choose low-noise ventilation equipment to avoid disturbing the staff during use.

Energy consumption: Choose ventilation equipment with lower energy consumption to reduce operating costs.

Reliability: Choose ventilation equipment with reliable quality and stable performance to ensure the stability and reliability of long-term use.

FAQ :

Q: Can you print our logos on tent?

* Yes. Customized logos can be print on the tent fabric according to your requirements.

Q: Is that factory price?

* Yes. We assure you all prices are based on factory.

Q: Does your tent be able to install repeatedly?

* Our tents can be assembled and dismantled and repeatedly with small transportation size. The lifespan of aluminium framework can reach 15-20 years, and 5-8 years for PVC fabrics depending on different conditions of usage.

Q: What documents are available?

* A full range documents including structural drawings, packing list, installation manual and relative certificates can be provided. Moreover, customs declaration is provided. We provide one-stop service for you.

Q: What size tent is necessary for your special event?

* A person must first determine tent usage. If a tent is being used for dining purposes and round tables are being used allow 10-12 square feet per person. If banquet style tables are being used allow 8-10 square feet per person. If the purpose is for cocktail service allow 5 to 6 square feet per person. Contact us for all your specific questions and more information on tent types.

Contact us :

Company:	Tendars technology Co.,Ltd
Address:	Room 904, No. 6, Hanxing 3rd Street, Zhongcun Street, Guangzhou, Guangdong, China
Contact person:	Amanda Chen
Tel:	0086-13640286461
Mobile(Wechat/Whatsapp):	+86 13640286461 / Amandachan8972
Web:	http://www.marquees-tent.com





Guangzhou Tendars Tent Co., Limited



0086 13640286461



amanda@marquees-tent.com



marquees-tent.com

No.319, 2nd building , 8th zone , Aoyuan city plaza , Zhongcun Street, Guangzhou, Guangdong, China