



Luxury White Aluminum Party Tents Fire Retardant DIN4 Used Event Tents For Sale Party Plus Tents And Events

Our Product Introduction

Basic Information

- Place of Origin: Guangdong
- Brand Name: Tendars
- Certification: ISO9001, SGS Coc, CE
- Model Number: Big tent
- Minimum Order Quantity: 25 square meters
- Price: Reconsideration
- Packaging Details: 1, The aluminium frame structure packed into the bubble film 2, the pvc fabric roof cover and sidewalls are packed into the PVC fabric carry bag; 3, Hardware packed into the box.
- Delivery Time: 18days or To be negotiated
- Payment Terms: L/C, T/T, Western Union, MoneyGram
- Supply Ability: 50000 Square Meters per Month




Product Specification

- Features: UV Resistant, Waterproof, Fire Retardant (DIN4102, B1, M2)
- Product Name: Types Of Tents For Parties
- Application: Weddings, Parties, Factories, Workshops, Exhibitions, Events, Etc
- Frame: Reinforced Aluminium Alloy 6061
- Roof Cover: PVC Coated Fabric, Blockout.850g/sqm
- Fabric Color: White, Red, Green, Clear Or Customized Color
- Fire-retardant Grade: M2,B1,DIN4
- Function: Can Be Assmebled To Bigger Or Smaller
- Highlight: **Fire Retardant Aluminum Party Tents, DIN4 Aluminum Party Tents**



More Images



for more products please visit us on marquees-tent.com

Product Description

Luxury White Aluminum Party Tents Fire Retardant DIN4 Used Event Tents For Sale Party Plus Tents And Events

Product Specification:

Type	Span width(m)	Bay spacing(m)	Eave height(m)	Ridge height(m)	Main frame profile (mm)
TDS-6	6	3	2.5	3.5	48X84X3
TDS-8	8	3	2.5	3.9	48X84X3
TDS-10	10	3	2.5	4.3	48X84X3/48X100X3
TDS-12	12	5	3	5.1	68X122X3
TDS-15	15	5	3	5.4	108X150X3
TDS-18	18	5	4	6.9	112X203X4
TDS-20	20	5	4	7.2	112X203X4
TDS-25	25	5	4	8.0	112X203X4
TDS-30	30	5	4	8.8	113X259X5
TDS-40	40	5	4	10.4	120X300X5
TDS-50	50	5	5	13	128X350X5

Glass walling system Glass walling system :

Available on all big tent structures, our lightweight integrated glass walling system is quick and easy to install. Apply to Available in large tent construction Our glass wall system integration is lightweight, quick and easy to install. The system works on the basis of four panels per 5m bay. The system operates on the principle of every 500 The basis for the four teams in Wan Wan Bay. The panels are secured by the simple configuration of the supplied anodised alloy hardware kit. All teams take this The anode alloy hardware kit is provided for simple configuration. The RODER HTS glass-walling system can be used in conjunction with, or without, our integrated flooring systems making it more flexible than other systems currently available on the market. The high-temperature superconducting roder glass wall system can be used with or without Having our integrated terrestrial system makes it more flexible to the market than other systems currently available. When the structure is set up on a grass or hardcore surface, the special ground tray sits directly on the ground spanning base-plate to base-plate A special plate directly spanning the substrate where the plate sits on the ground when the structure is set on a grass or hard surface The ground. To add flexibility, glass panels can be exchanged for ABS panels and single or double door units. For added flexibility glass panels are convertible ABS plate Single or two-door units. These may be added within any bay section as both the glass walling and ABS walling systems use the same hardware These may be added in any bay section as both wall glass walls and ABS systems are used Same hardware components.

Adding glass walling to your existing or new structure enhances the overall visual effect - giving the structure the feel of a permanent building with the flexibility of being easily re-Add a glass curtain to make an existing or new structure improve the overall visual effect - let the knot The sense of a permanent building that can be easily reconstituted to be flexible.

To protect your investment RODER HTS supplies specially designed galvanised steel transportation stillages for our glass walling and door systems. To protect your investment Rohde HTS supplies galvanized steel sheet Menté Don't design a transport slide conveyor system for our glass walls and. General specification General specification norm

Colour: Colour White or anodised aluminium Glass. Colour: white or anodised aluminium thickness: glass thickness 8.8mm laminated security glass 8.8mm All-glass Dimensions: Dimensions 1,187mm x 3,77m (4m side height) 1,187mm x 3,77m 4m side height 1,187mm x 2,77m (3m side height) 1,187mm x 2,77 m 3 m side height Flame retardant According to DIN 4102, B1, BS, M1 According to DIN 4102 B1 UK BS M1 Material of money supply specification Aluminium frame or UPVC with steel reinforcements plastic steel with aluminum frame or rebar

RFQ :

Q1. Are you factory or trade company?

We are direct factory.

Q2. What is your Payment terms?

T/T is available.

Q3. When will you ship the orders?

Once the design of tent is confirmed,we will arrange production plan,and inform you of the leadtime.generally it takes about 7-25 working days.

Q4. What is the total price include freight?

The total price is based on the design of the product and the requirement of the customer,all subject to the final calculation.



Guangzhou Tendars Tent Co., Limited

☎ 0086 13640286461

✉ amanda@marquees-tent.com

🌐 marquees-tent.com

No.319, 2nd building , 8th zone , Aoyuan city plaza , Zhongcun Street, Guangzhou, Guangdong, China