



Commercial Marquee Wedding Tents For Outdoor Different Tents For Weddings Modern Tent Rentals

Our Product Introduction

Basic Information

- Place of Origin: Guangdong
- Brand Name: Tendars
- Certification: ISO9001, SGS Coc, CE
- Model Number: Big tent
- Minimum Order Quantity: 25 square meters
- Price: Reconsideration
- Packaging Details: 1, The aluminium frame structure packed into the bubble film 2, the pvc fabric roof cover and sidewalls are packed into the PVC fabric carry bag; 3, Hardware packed into the box.
- Delivery Time: 18days or To be negotiated
- Payment Terms: L/C, T/T, Western Union, MoneyGram
- Supply Ability: 50000 Square Meters per Month





Product Specification

- Product Name: Wedding Tent Cost
- Aluminum Profile: Aluminum Alloy Profile Extruded
- Oem/odm: Available
- Cover Material: Double PVC-coated Fabric, waterproof, fireproof, sunproof
- Color: White/red/blue/green/yellow/black Etc.
- Max Allow Wind Speed: 100km/hour
- Certificates: TUV.SGS.CE ISO9001
- Usage: Wedding/party/event/exhibition/church Etc.
- Highlight: **Commercial Marquee Wedding Tents, Marquee Wedding Tents 40x100**



More Images



for more products please visit us on marquees-tent.com

Product Description

Commercial Marquee Wedding Tents For Outdoor Different Tents For Weddings Modern Tent Rentals

Product Specification:

Span Width	3m/4m/5m/6m/8m/9m/10m/12m
Ridge Height	3.2m/3.4m/3.6m/3.7m/4.m/4.3m/4.4m/4.8m
Longest Component	2.9m/3.9m/4.9m/3.6m/4.3m/4.8m/5.3m/6.3m
Side Height	2.6m
Roof Pitch	20°
Bay Distance	3m/5m
Maximum Length	No limit
Main Profile	84X48X3mm/100X48X3mm/122X68X3mm aluminum alloy
Frame Material	High reinforced aluminum, anti-rust surface, GB/T 6061- T6 standard, Surface oxidation; Film thickness > 10µm
Fabric Material	850 g/m ² and 650 g/m ² double PVC-coated polyester, flame retardant, UV resistance, waterproof, comply with DIN 4102 B1, M2 (German standard), Applicable temperature range: - B0°C to +70 °C
Connection Part	All steel parts are galvanized steel, hot-dipped and not easily rusted, and all come with rust prevention process.
Maximum Wind Limit	80~100km/h
Eave Connection	Direct insert style
Reinforce Method	Portal beam

The composition of the tent :

The structure consists of a metal structure and a canopy body. The metal structure is used for both support and structure. A canopy structure, and the canopy body is used to improve the metal structure, generally flash a good canopy. A surname The metal structure is composed of metal raw materials, aluminum alloy main structure and aluminum. There are two kinds of steel, aluminum alloy is slightly stronger than aluminum alloy steel. And the canopy, The primary raw material of the canopy body is tarpaulin, but in the canopy structure, Canopy body is divided into top cloth, enclosing cloth and wrapping cloth three, the top cloth is the roof of the canopy. Generally speaking, the raw materials here will be selected in the manufacturing process of slightly better quality Tarpaulin, about gram weight of 750g/ square meter or more, woven 1000*1000, density 20*20, Think about the shading function together, this cloth will usually be a black cloth (a kind of cloth in tarpaulin), The life of this type of top cloth is usually around five years. The girth, that is, the cloth that is surrounded all around, The material weight of the tarpaulin used in the covering cloth is 650g/ square meter, woven 2000*2000, density 20*20. Then there is the wrapping cloth, which is usually used as the whole tent body. The weight is light, in 600g/ square meter can be satisfied with the overlapping edge of this cloth. weaving 1000*1000, density 18*20. These are more detailed parameters of common sense, except In addition, we usually pay attention to the size of the tent specification information, is still divided into two Species said, small tent and medium tent. Small tent width, usually 3m, 4m, 6m, 8m, 9m, 10m and 12m, the length of 3m/ group added, this type of tent is usually used for family gatherings, parties, Weddings, ceremonies, exhibitions, warehouses, etc. The width of the medium canopy is relatively too wide, Usually there are 15m, 18m, 20m, 21m, and the length is added in 5m/ group. Type of shelter It is used more in trade fairs, sports events, festivals, storeroom storage, cars Car shows and so on. Needless to say about the large, the use of large tents is usually less, Encounter customized large tents, usually according to the completion of the application of professional customization needs.

FAQ :

1. Is sample order acceptable at the very beginning? Can I specify the color? What is the cost?

Yes, it is acceptable, welcome your

sample order,we understand you like to see it in real and test its quality before placing bulk order. Yes,although one sample needed, you can specify the color. As just produce a sample,the labor cost and other expense will be much higher,there will be an extra sample charge

2. Can your tent move to the other place after set up?

A: Yes, the mainframe of our tent is aluminum, so it is light in weight but with high strength, that is very easy to set up and dismantle.

3. How can I go to visit your company?

A: Our company is located in Guangzhou, south china city, when you in Guangzhou you can take the Metro 3 to Panyu Square then we pick you up there or you can take the taxi to our factory.



Guangzhou Tendars Tent Co., Limited

☎ 0086 13640286461

✉ amanda@marquees-tent.com

🌐 marquees-tent.com

No.319, 2nd building , 8th zone , Aoyuan city plaza , Zhongcun Street, Guangzhou, Guangdong, China