



Outdoor Heavy Duty Wedding Marquee Tents UV Proof Wind Resistance Outdoor Wedding In Tent

Our Product Introduction

Basic Information

- Place of Origin: Guangdong
- Brand Name: Tendars
- Certification: ISO9001, SGS, Coc, CE
- Model Number: Big tent
- Minimum Order Quantity: 25 square meters
- Price: Reconsideration
- Packaging Details: 1, The aluminium frame structure packed into the bubble film 2, the pvc fabric roof cover and sidewalls are packed into the PVC fabric carry bag; 3, Hardware packed into the box.
- Delivery Time: 18days or To be negotiated
- Payment Terms: L/C, T/T, Western Union, MoneyGram
- Supply Ability: 50000 Square Meters per Month



Product Specification

- Product Name: Buy Tent For Wedding
- Aluminum Profile: Aluminum Alloy Profile Extruded
- Sidewall Material: Glass Or Fiber Glass Wall, ABS Hard Wall
- Cover Material: Double PVC-coated Fabric, waterproof, fireproof, sunproof
- Color: White/red/blue/green/yellow/black Etc.
- Lifespan Of Frame: 15 To 20 Years If Well Maintained
- Lifespan Of Cover: 5 To 10 Years If Well Maintained
- Usage: Wedding ,celebration ,festival ,fashion Show Exhibition ,etc.
- Highlight: **Wedding Marquee Tents UV Proof, Wind Resistance Wedding Marquee Tents**



More Images



Product Description

Outdoor Heavy Duty Wedding Marquee Tents UV Proof Wind Resistance Outdoor Wedding In Tent

Product Specification:

The bay distance of 5m of length.

Clear span	Tent size for every case	Material	Profile size	People capacity
10mx30m	10*5*4*5.6m	T6061-T6	122*68*3mm	200
12mx30m	12*5*4*6.1m	T6061-T6	122*68*3mm	240
15mx30m	15*5*4*6.4m	T6061-T6	166*88*3mm	300
18mx30m	18*5*4*7.2m	T6061-T6	203*110*4.5mm	360
21mx30m	21*5*4*7.4m	T6061-T6	203*110*4.5mm	420
25mx30m	25*5*4*8m	T6061-T6	203*110*4.5mm	500
30mx30m	30*5*4*8.8m	T6061-T6	254*120*5mm	600
40mx30m	40*5*4*10.3m	T6061-T6	300*125*6mm	800
50mx30m	50*5*4*12m	T6061-T6	300*125*6mm	1000

The difference between tents and tents is mainly the following:

1. Different meanings:

Tent: mobile environment, used for industrial warehousing, logistics distribution, various outdoor exhibitions, sports events, Tourism and leisure, business parties, celebrations, business promotion, military use and disaster relief and other temporary activities tent.

Tent: A shelter that is propped up on the ground to shelter from the sun, wind and rain and for temporary living. A lot of canvas, along with support things, can

Remove at any time for transfer. The tent is carried in the form of parts and assembled after arriving at the site, so various parts and tools are needed.

Understand the name and use of each component, familiar with the structure of the tent, in order to quickly and easily set up the tent.

2. The main materials are different:

Tent: The main structure of the tent is composed of three basic parts, aluminum alloy, steel, tarpaulin.

Aluminum alloy: mainly used for structural parts.

The main frame of the tent is high strength hollow aluminum alloy structure, steel structure or steel aluminum structure.

The aluminum alloy used for the structural frame of the tent is usually 6061 or 6063.

The beauty and weather resistance of aluminum alloy often meet the requirements of middle and high grade tents.

Steel: mainly used for building structural nodes

And infrastructure parts.

Common specifications for the national standard Q235B,

Steel components ensure the durability of the canopy structure,

Corrosion resistance, steel using hot dip zinc or paint,

The connections between components are often welded, bolted or riveted.

The internal force and strain of a single structure or component form an overall structural effect.

So as to form the space force system of the tent,

Ensure the safety and stability of the structure.

Tarpaulin: main for the enclosure. PVC synthetic fiber double blade coated cloth (commonly known as: blade coated PVC).

The tarpaulin has flame retardant, tensile resistance, tear resistance,

Rain and UV proof, self-cleaning performance,

Good performance of light permeability

Fire rating reached the current national standard GA91-1995 standard,

PVC adopts high frequency welding technology,

The wind resistance of the tent can reach 80-100 km/h.

The main structures of membrane materials for construction are as follows:

The base material of PVC building film material is polyester,

FAQ :

1.Is that factory price?

Yes, we assure you all the prices are based on factory.

2.What's the suitable size to choose?

The tent size depends on the people to accommodate.

Normally, if tables and chairs is included, we suggest 1.3-1.5square meters for each person. Chairs only, 1 square meter for each person; If no chairs and tables, 0.6sqm for each one.

3.What's the life span of the tent? Is your tent strong and stable enough?

The tent aluminum structure can be used over 20 years, fabric is about 3-8 years under normal condition.

The structure are manufactured with high impact extruded anodized aluminum, so it's safe and strong enough to resist big wind.



Guangzhou Tendars Tent Co., Limited

☎ 0086 13640286461

✉ amanda@marquees-tent.com

🌐 marquees-tent.com

No.319, 2nd building , 8th zone , Aoyuan city plaza , Zhongcun Street, Guangzhou, Guangdong, China