

Large 100 300 500 People Event Marquee Tent Outdoor Aluminum Party Reception Tents Marquee Hire Business

Our Product Introduction

for more products please visit us on marquees-tent.com

Basic Information

- Place of Origin: Guangdong
- Brand Name: Tendars
- Certification: ISO9001, SGS Coc, CE
- Model Number: Big tent
- Minimum Order Quantity: 25 square meters
- Price: Reconsideration
- Packaging Details: 1, The aluminium frame structure packed into the bubble film 2, the pvc fabric roof cover and sidewalls are packed into the PVC fabric carry bag; 3, Hardware packed into the box.
- Delivery Time: 18days or To be negotiated
- Payment Terms: L/C, T/T, Western Union, MoneyGram
- Supply Ability: 50000 Square Meters per Month




Product Specification

- Product Name: Reception Tents
- Aluminum Profile: Hard Pressed Extruded Aluminum Alloy
- Side Wall: Soft PVC Walls, Sandwich Panel, Glass Wall
- Tent Roof Fabric: Heavy Duty White 850g/sqm PVC Fabric
- Roof Pitch: 18° / 20°
- Lifespan Of Frame: 15 To 20 Years If Well Maintained
- Lifespan Of Cover: 5 To 10 Years If Well Maintained
- Logo: Customized
- Highlight: Large outdoor event marquee tent, Aluminum party reception tent, 500 people marquee hire business



More Images



Our Product

Product Description

Large 100 300 500 People Event Marquee Tent Outdoor Aluminum Party Reception Tents Marquee Hire Business

Product Specification:

Product Name	Large 100 300 500 People Tent Outdoor China Aluminum Party Reception Tents For Events
Span Width	3m/4m/5m/6m/8m/9m/10m/12m/15m/18m/20m/25m/30m/ 40m/50m
Ridge Height	3.2m/3.4m/3.6m/3.7m/4.m/4.3m/4.4m/4.8m/6.4m/6.9m/7.2m/ 8.0m/8.9m/10.6m/12.3m
Longest Component	2.9m/3.9m/4.9m/3.6m/4.3m/4.8m/5.3m/6.3m/ 8m/9.6m/10.7m
Side Height	2.6m/3m/4m
Roof Pitch	18°/20°
Bay Distance	3m/5m
Maximum Length	No limit
Main Profile	84X48X3mm/100X48X3mm/122X68X3mm/166X88X3mm/ 204X110X4mm/256X113X5mm/300X125X6mm/350X125X8mm aluminum alloy
Frame Material	High reinforced aluminum,anti-rust surface, GB/T 6061-T6 standard,Surface oxidation;Film thickness>10jμm
Fabric Material	850g/m ² double PVC-coated polyester,flame retardant,UV resistance,waterproof,comply with DIN 4102 B1,M2 (German standard),Applicable temperature range:-30°C to +70 °C
Connection Part	All steel parts are galvanized steel,hot-dipped and not easily rusted,and all come with rust prevention process.
Maximum Wind Limit	80 ~100km/h
Eave Connection	Clip-fix style
Reinforce Method	Cross-fix

Tent accessories Indispensable tent floor :

Tents are usually built in outdoor places, so it is inevitable to encounter uneven or unclean ground. In pursuit of Quality of the ground effect, more and more people use wood flooring in the tent, after the use of wood flooring in the tent, the ground is more flat Whole, beautiful. Wood flooring has its own unique advantages that other floor systems cannot achieve.

Advantages of wood flooring:

- 1, beautiful and natural, wood flooring natural and beautiful, can be perfectly integrated with nature;
- 2, no pollution, wood is the most typical green products, itself has no pollution sources;
- 3, light and strong, wood floor as a ground material can reflect its advantages;
- 4, easy to process, flexible use;
- 5, good thermal insulation, wood is not easy to conduct heat, the thermal conductivity of concrete is very high;
- 6, adjust the temperature, wood can absorb moisture and evaporation;
- 7, not easy to condensation, when the weather is wet, or when the temperature drops, it will not produce surface formation of water-like sweating phenomenon;
- 8, strong durability, the shock resistance and corrosion resistance of wood by scientific and technological treatment is not inferior to other building materials.

At present, three kinds of flooring are used more, and customers can use them freely according to cost requirements. One is an ordinary wood floor:

Easy to install. The price will be relatively affordable. One is tape box wood floor: modular, easy to install, stylish appearance
High grade. It has a specific anti-skid function, and can also be installed when the ground is uneven. One is VIP card wood floor: high
The end is atmospheric and high-grade, and there is an aluminum alloy frame in the middle. Laid on the aluminum alloy girder, can absolutely
ensure the floor flat and bearing.
There are also multiple options such as stage wood flooring.

FAQ :

1: Can you develop products with our drawing?

Yes, please offer your drawing with technical requirements

2: What's your Delivery Time?

Normally 20 working days, please confirm with us before order!

3: What's the Payment Terms?

30% deposit balance to be paid before shipment

7: How you pack products?

Aluminum frame packed in air bubble film, roof and sidewall in professional
PVC carry bag, or under your requirements.

8: What's your available port of Shipment?

We usually export through SHANGHAI port



Guangzhou Tendars Tent Co., Limited

☎ 0086 13640286461

✉ amanda@marquees-tent.com

🌐 marquees-tent.com

No.319, 2nd building , 8th zone , Aoyuan city plaza , Zhongcun Street, Guangzhou, Guangdong, China