



## Anchored Executive Party Marquee Tents Extruded Aluminum Alloy Frame European Standard System Canopy Structure

Our Product Introduction

### Basic Information

- Place of Origin: Guangdong, China
- Brand Name: Tendars
- Certification: ISO 9001:2015, CE, SGS
- Model Number: Tendars
- Minimum Order Quantity: 100sqm
- Price: \$35/sqm
- Packaging Details: Steel frame wrapped in foam and PE film, PVC cover folded in waterproof bag, export-grade wooden pallet
- Delivery Time: 10-25 working days for heavy duty orders
- Payment Terms: T/T,L/C,Western Union
- Supply Ability: 200 Sets per Month



### Product Specification

- Cover Material: 950gsm PVC Laminated Polyester
- Frame Construction: 6061-T6 Aluminum Alloy Hard Anodized
- Eave Height: 2.5m – 3.5m
- Wind Resistance: 85 Km/h
- Ridge Height: 3.5m – 5.0m
- Snow Load: 0.35 KN/m<sup>2</sup>
- Highlight: **950gsm PVC Heavy Duty Tent, Extra Thick Cover Party Marquee, UV Resistant Waterproof Construction**

for more products please visit us on [marquees-tent.com](http://marquees-tent.com)

## Product Description

### Extra Thick 950gsm PVC Heavy Duty Construction Party Marquee Tent Aluminum Frame UV Resistant Waterproof Cover

#### Extra Thick 950gsm PVC Construction Party Marquee Tent

Our premium heavy duty construction party marquee tent is engineered to deliver exceptional structural integrity and long-term reliability. Built with 6061-T6 aluminum alloy hard anodized and 950gsm PVC laminated polyester, this tent is designed to withstand demanding environmental conditions while providing spacious, weather-protected event space.

#### Heavy Duty Construction Features

**Robust Frame Construction:** 6061-T6 Aluminum Alloy Hard Anodized provides superior strength-to-weight ratio and excellent corrosion resistance

**Premium Cover Material:** 950gsm PVC Laminated Polyester with double-stitched seams, welded joints, and reinforced stress points

**Wind Resistance:** Engineered and tested to withstand wind speeds of up to 85 km/h with proper anchoring

**Snow Load Capacity:** Structural design rated for 0.35 kN/m<sup>2</sup> snow load accumulation

**Modular Bay System:** Width range 4m - 12m, length extendable 3m - 25m in 3m increments

**Professional Engineering:** Each structure undergoes computational structural analysis for your specific site conditions

**Hot-Dip Galvanized Connectors:** All steel connectors and fasteners are hot-dip galvanized to prevent rust

**Reinforced Eaves and Ridges:** Additional bracing at all critical load transfer points

#### Heavy Duty Construction Standards

**Material Selection:** Only certified structural-grade aluminum alloy and galvanized steel with full material traceability

**Weld Inspection:** All welded joints undergo visual and dimensional inspection per ISO 3834 standards

**Load Testing:** Frame assemblies are subjected to static load testing at 1.5x design load

**Cover Testing:** PVC fabric tested for tensile strength, tear resistance, and UV aging per ISO 1421

**Pre-Delivery Assembly:** Complete trial assembly in factory to verify fit, alignment, and structural integrity

**Quality Documentation:** Mill certificates, test reports, and inspection records provided with each order

#### Applications

Ideal for outdoor weddings, corporate events, trade exhibitions, music festivals, temporary warehousing, disaster relief shelters, and sports facilities requiring heavy duty structural performance and extended service life.

#### Technical Specifications

Frame Construction	6061-T6 Aluminum Alloy Hard Anodized
Cover Material	950gsm PVC Laminated Polyester
Width Range	4m - 12m
Length Range	3m - 25m
Eave Height	2.5m - 3.5m
Ridge Height	3.5m - 5.0m
Wind Resistance	Up to 85 km/h
Snow Load	0.35 kN/m <sup>2</sup>

Contact our engineering team for site-specific structural calculations and heavy duty construction specifications.



Guangzhou Tendars Tent Co., Limited

0086 13640286461

amanda@marquees-tent.com

marquees-tent.com

No.319, 2nd building, 8th zone, Aoyuan city plaza, Zhongcun Street, Guangzhou, Guangdong, China

