



## UV Resistant 850gsm PVC Party Marquee Tent Fabric Double Coated Roof Cover Five Year Outdoor Durability Canopy

Our Product Introduction

### Basic Information

- Place of Origin: Guangdong, China
- Brand Name: Tendars
- Certification: ISO 9001, CE, SGS Material Test, UV Aging Test Report
- Model Number: TDT-UV850
- Minimum Order Quantity: 25 Square Meters
- Price: USD 38-68 per Square Meter
- Packaging Details: Fabric panels rolled on cardboard tubes with UV-protective outer wrap; interleaving tissue prevents surface marking during storage
- Delivery Time: 10-18 working days
- Payment Terms: T/T, L/C, Western Union, PayPal
- Supply Ability: 50000 Square Meters per Month



### Product Specification

- Fabric Weight: 850g/sqm (roof) / 650g/sqm (sidewall)
- Coating: Double Sided PVC Coating
- UV Stabilizer: Titanium Dioxide UV Inhibitor Additive
- Tear Strength: Warp 3200N/5cm, Weft 2800N/5cm
- Tensile Strength: Warp 4200N/5cm, Weft 3800N/5cm
- Temperature Range: -30°C To +70°C
- Anti-Mildew: Yes, ISO 846 Certified
- Warranty: 2 Years On Fabric UV Degradation
- Highlight: **UV resistant PVC marquee tent fabric, 850gsm double coated roof cover, five year durable outdoor canopy**

for more products please visit us on [marquees-tent.com](http://marquees-tent.com)

## Product Description

### UV-Resistant 850g/sqm Double Coated PVC Party Marquee Tent Fabric

The difference between a tent that lasts one season and one that lasts five years is in the fabric. Our premium Party Marquee Tent features 850g/sqm double coated PVC polyester fabric with titanium dioxide UV stabilizer additive, engineered for sustained outdoor exposure in high-UV environments including Southern Europe, Middle East, Australia, and tropical regions. Independent SGS laboratory testing confirms tear strength of 3200N/5cm warp and 2800N/5cm weft, tensile strength of 4200N/5cm warp and 3800N/5cm weft, and anti-mildew performance per ISO 846. The double-sided PVC coating ensures water resistance exceeding 1000mm hydrostatic pressure, keeping your event dry even in torrential rain.

#### Fabric Technical Specifications

Base fabric: 1000D x 1000D high tenacity polyester yarn, 23x23 threads per inch

Coating: Both sides PVC with UV stabilizer and anti-fungal agent

Surface finish: Glossy lacquer topcoat for self-cleaning in rain

Cold crack resistance: No cracking at -30°C

High frequency welding compatible for seam construction

Color fastness: Grade 4-5 blue wool scale after 2000 hours QUV accelerated aging

#### Long-Term Durability Testing

Our 850g/sqm fabric has undergone 5000 hours of QUV accelerated weathering testing (equivalent to approximately 5 years of Northern European outdoor exposure) with minimal tensile strength loss and color change. SGS UV aging test reports and material certifications are provided with every order.



Guangzhou Tendars Tent Co., Limited



0086 13640286461



amanda@marquees-tent.com



marquees-tent.com

No.319, 2nd building , 8th zone , Aoyuan city plaza , Zhongcun Street, Guangzhou, Guangdong, China