

A-Frame Glass Wall Gala Marquee Tent Car Launch Canopy Laminated Tempered Glass Structure

Our Product Introduction

Basic Information

- Place of Origin: Guangdong, China
- Brand Name: Tendars
- Certification: ISO9001, SGS, COC, CE
- Model Number: TDS-AF25GX60
- Minimum Order Quantity: 300 square meters
- Price: USD 78-115 / Square Meter
- Packaging Details: Glass in edge protected plywood A-frames with EPE interleaves, mullions felt wrapped, frame beams in timber cradles, no double stacking
- Delivery Time: 25 days production after deposit and drawing approval. Sea freight time depends on your destination port. Installation time varies with the project and site access.
- Payment Terms: T/T 40% deposit, 50% before loading, 10% after glass check; L/C at sight
- Supply Ability: 30000 Square Meters per Month for glazed structures



Product Specification

- Span Width: 25m
- Length: 60m (12 Bays Of 5m)
- Eave Height: 4m
- Ridge Height: 7.2m
- Floor Area: 1500 Square Meters
- Area Per Guest: 1.2 To 2 Sqm, 750 To 1250 Guests
- Main Frame: 203 X 112 X 4mm Aluminium 6061/T6
- Base Plate: 350 X 350mm Hot Dip Galvanised Steel
- Glass Wall: 6+6mm Laminated Tempered, 1.2 X 2.5m Panels, 65 Kg Each
- Door: 4m Double Sliding Glass With Soft Close
- Wind Load: 0.5 KN/sqm
- Frame Life Span: 20+ Years
- Production Time: 25 Days
- Highlight: **A-Frame Glass Wall Marquee Tent**,

for more products please visit us on marquees-tent.com

Our Product Introduction

for more products please visit us on marquees-tent.com

Product Description

25m x 60m glass wall gala hall

Nobody books a glass marquee for the roof. They book it so a car on a turntable is reflected in sixty metres of glass at eleven at night.

Details

25m span gives depth for a 20m turntable plus a 5m press area, with two 6m side aisles for guests walking the car. The 7.2m ridge clears a 6m lighting truss and a large format video wall without the roof appearing in the shot.

Area guide: 1.2 to 2 sqm per guest. 1500 sqm takes 750 at a seated gala or 1250 standing.

Glass sits on a continuous steel base rail levelled to plus or minus 2mm, not on the fabric line. If the base is out, the glass will not hang plumb and the sliding doors will not run.

Size range and options

Span: 25m. Range 10m to 40m.

Length: 60m, any multiple of 5m.

Glass: one long side, two sides, or three sides. Rear wall usually stays fabric.

Doors: 4m sliding glass, or 3m hinged double doors at each gable.

Extras: ivory ceiling lining, cassette floor, floor boxes every 5m, LED wash bars, duct penetrations for HVAC.

Main components

Frame. 203 x 112 x 4mm aluminium 6061/T6, hot dip galvanised connectors, 350 x 350mm base plates. 20+ years.

Glass. 6mm tempered + 1.52mm PVB + 6mm tempered, 1200 x 2500mm panels at 65kg. Anodised aluminium mullions at 1.2m centres carry the panels.

Covers. 900gsm opaque white PVC roof with blackout lining down to the glass line, so the glass reads as a clean lit plane from outside.

Specification

Item	Specification
Clear span / length	25m / 60m, 12 bays of 5m
Eave / ridge	4.0m / 7.2m
Frame	203 x 112 x 4mm aluminium 6061/T6
Glass	6+6mm laminated tempered on a levelled steel base rail
Roof	900gsm opaque white PVC with blackout lining
Wind load	0.5 kN/sqm, glass grid checked separately
Frame life	20+ years

Climate

1500 sqm of glass in summer reaches 38 C by mid afternoon without cooling. We pre-install four duct penetrations at eave level for 40kW units. The units themselves are cheaper sourced locally and serviced locally - the penetrations and load frame are the parts that cannot be retrofitted.

Production and installation

25 days production after deposit and glass drawing approval, plus freight. Glass crates cannot be double stacked, so plan the unload. Twelve workers, about ten days; glass goes in only after the roof is closed. *Installation is quoted separately: labour, air tickets, visa, food and accommodation are paid by the buyer. Send us the site address and we confirm crew size, days and cost.*

FAQ

Is the glass safe for public events? Yes, laminated tempered breaks into a bonded sheet rather than falling shards. We supply the impact test certificates.

Can the glass be replaced if broken? A single panel, in under two hours, from the outside with suction lifters.

Do we need a floor? Not compulsory, but a launch on 1500 sqm of grass reads very differently. Cassette floor at USD 22 to 28 per sqm.

Guangzhou Tendars Tent Co., Limited

0086 13640286461 amanda@marquees-tent.com marquees-tent.com

No.319, 2nd building , 8th zone , Aoyuan city plaza , Zhongcun Street, Guangzhou, Guangdong, China